

### TECHNICAL DATA SHEET



## Retarding mortar additive

# MTC - Mortar VZ

Art. - No. 05.102.

#### **APPLICATION AREA:**

- To produce trowelable ready-mixed mortar.
- To produce ready-mixed mortar with a considerably delayed processing time.

#### **CHARACTERISTIC:**

MTC – Mortar VZ is a retarding mortar additive for producing ready-mixed mortar. It is used together with MTC – Mortar LP or MTC – Mortar LPS.

MTC - Mortar VZ enables

• a long-lasting delay of the reactions of the cement in the mortar by up to 48 hours.

#### **TECHNICHAL SPECIFICATIONS:**

Basic raw materials Saccharose / phosphate

Colour: brown
Form: Liquid
pH value 8.0 – 12.0
Density (with 20 °C): 1.13 ± 0.02 g/ml
Processing temperature: Above + 5 °C
Shelf life: c. 12 months

Storage: Store away from direct sunlight and frost. Protect from

impurities

#### **DOSAGE:**

Recommended dosage: 0.7 - 1.5 M % of the cement weight

The duration of delay is controlled by the dosage. Establish the

correct dosage by carrying out preliminary tests.





## TECHNICAL DATA SHEET

#### **PROCESSING INFORMATION:**

- Add the MTC Mortar VZ to the mortar's mixing water. If this is not possible, the MTC Mortar VZ can also be thoroughly mixed in to the finished ready-mix mortar.
- Always ensure a sufficient mixing time.
- To prevent the dehydration of the ready-mixed mortar due to the sun, heat and wind, the
  ready-mixed mortar should be protected from direct sunlight and also covered or wetted in
  order to protect it from drying out too quickly.
- Absorptive masonry must be thoroughly pre-wetted.

#### **WORK SAFETY:**

- Not a hazardous substance as defined by the ordinance on hazardous substances
- Not hazardous goods as defined by transport regulations
- WHC 1 (self assessment) little risk of pollution
- Please refer to the safety data sheet

#### **FORM OF DELIVERY:**

35 kg PVC can - gfn 240 kg Poly drum gfn 1200 kg Container net Tanker delivery upon request

#### NOTE:

Always observe general work hygiene when using our products. The raw materials we process and the products we produce are subject to strict factory inspections. We reserve the right to make changes that signify a technical advance. All the information applies to the normal case scenario, and has been given to the best of our knowledge. We cannot be held legally liable as a result of the information included in this leaflet. It is stressed that our products and the procedure must be tested for suitability with your circumstances.

EFFECTIVE: 07/11



Tel: 0049 9324/9191-0 Fax: 0049 9324/9191-55 info@mtc-chemie.com