

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Systopp - Colerit EH 2 (Resin)

Print date: 19.03.2020

Product code: 43.600.100

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Systopp - Colerit EH 2 (Resin)

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Building and construction work.
Coatings and paints, fillers, putties, thinners

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	KNOPP GmbH.	
Street:	Adolf - Oesterheld - Str. 1	
Place:	D-97337 Dettelbach	
Telephone:	+49932491990	Telefax: +499324919966
e-mail:	info@knopp-chemie.com	
Internet:	www.knopp-chemie.com	

1.4. Emergency telephone number:

Tox Info Suisse Tel.: 145
Giftnotruf Berlin (24 h): 030 30686700

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard categories:
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Respiratory or skin sensitisation: Skin Sens. 1
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.

2.2. Label elements**Hazard components for labelling**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
100 %

Signal word: Warning
Pictograms: GHS07-GHS09

**Hazard statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Systopp - Colerit EH 2 (Resin)

Print date: 19.03.2020

Product code: 43.600.100

Page 2 of 8

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P391 Collect spillage.
 P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

Restricted to professional users.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 100 %	
25068-38-6	Xi - Irritant, N - Dangerous for the environment R36/38-43-51-53	95 - <= 100 %
603-074-00-8	Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H319 H315 H317 H411	

Full text of R, H and EUH phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 Medical treatment necessary.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Systopp - Colerit EH 2 (Resin)

Print date: 19.03.2020

Product code: 43.600.100

Page 3 of 8

5.2. Special hazards arising from the substance or mixture

The product itself does not burn.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

7.3. Specific end use(s)

siehe Abschnitt 1.2 *

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Occupational exposure controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
Respiratory protection necessary at: Handling larger quantities.
Suitable respiratory protective equipment: gas filtering equipment (EN 141). Combination filter device (DIN EN 141).. *
Filtering device with filter or ventilator filtering device of type: AX *

Systopp - Colerit EH 2 (Resin)

Print date: 19.03.2020

Product code: 43.600.100

Page 4 of 8

Hand protection

Single-use gloves. NBR (Nitrile rubber).
Breakthrough times and swelling properties of the material must be taken into consideration.
penetration time (maximum wearing period): 30 min < BTT < 480 min (BTT = Break Through Time) *
Thickness of glove material: < 0,4 mm *
German Industry Norms (DIN) / European Norms (EN): DIN EN 374 *

Eye protection

Suitable eye protection: Tightly sealed safety glasses.
German Industry Norms (DIN) / European Norms (EN): DIN EN 166 *

Skin protection

Suitable protective clothing: Single-use suit. Overall. Boots.
Only wear fitting, comfortable and clean protective clothing.
Take off immediately all contaminated clothing.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	light yellow transparent
Odour:	characteristic

Test method**Changes in the physical state**

Initial boiling point and boiling range:	>200 °C
Flash point:	150 °C
Ignition temperature:	> 460 °C
Density (at 20 °C):	1,14 g/cm ³
Water solubility:	insoluble

9.2. Other information

Solid content:	100 %
----------------	-------

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and handled correctly.

10.2. Chemical stability

In case of warming: Polymerization.

10.3. Possibility of hazardous reactions

Reacts with : Alkalis (alkalis). Amines.

10.4. Conditions to avoid

Do not freeze.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. aldehydes.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No information available.

Systopp - Colerit EH 2 (Resin)

Print date: 19.03.2020

Product code: 43.600.100

Page 5 of 8

Acute toxicity

No information available.

Specific effects in experiment on an animal

No information available.

Irritation and corrosivity

Irritating to eyes. After skin contact: irritant.

Sensitising effects

May cause sensitization by skin contact.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. May cause heritable genetic damage.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Product is biodegradable with difficulty.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

There are no data available on the mixture itself.

12.6. Other adverse effects

There are no data available on the mixture itself.

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. Waste disposal according to EC Directives 75/442/EEC and 91/689/EEC on waste and hazardous waste in their latest versions. *

Waste disposal number of waste from residues/unused products

080499 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); wastes not otherwise specified

Waste disposal number of used product

080499 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); wastes not otherwise specified

Waste disposal number of contaminated packaging

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Systopp - Colerit EH 2 (Resin)

Print date: 19.03.2020

Product code: 43.600.100

Page 6 of 8

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Waste disposal according to EC Directives 75/442/EEC and 91/689/EEC on waste and hazardous waste in their latest versions. *

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Classification code: M6
Special Provisions: 274 335 601
Limited quantity: 5 L
Transport category: 3
Hazard No: 90
Tunnel restriction code: E
Other applicable information (land transport)
E1

Inland waterways transport (ADN)

14.1. UN number: UN3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Classification code: M6
Special Provisions: 274 335 601
Limited quantity: 5 L
Other applicable information (inland waterways transport)
E1

Marine transport (IMDG)

14.1. UN number: UN3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Special Provisions: 274, 335
Limited quantity: 5 L
EmS: F-A, S-F
Other applicable information (marine transport)
E1

Air transport (ICAO-TI/IATA-DGR)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Systopp - Colerit EH 2 (Resin)**

Print date: 19.03.2020

Product code: 43.600.100

Page 7 of 8

14.1. UN number:	UN3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Special Provisions:	A97 A158
Limited quantity Passenger:	30 kg G
IATA-packing instructions - Passenger:	964
IATA-max. quantity - Passenger:	450 L
IATA-packing instructions - Cargo:	964
IATA-max. quantity - Cargo:	450 L
Other applicable information (air transport)	
E1	
Passenger-LQ: Y964	

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). *

Jugendarbeitsschutzverordnung (ArGV 5, SR 822.115): Jugendliche bis zum vollendeten 18. Altersjahr dürfen bei ihrer Arbeit nur dann mit dieser Zubereitung in Kontakt kommen oder dieser ausgesetzt werden, sofern das Bundesamt für Berufsbildung und Technologie (BBT) oder das Staatssekretariat für Wirtschaft (SECO) eine Ausnahme bewilligt hat.

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For this mixture a chemical safety assessment has been carried out.

SECTION 16: Other information**Changes**

* Data changed compared with the previous version

Die vorliegende Ausgabe des Sicherheitsdatenblatts ersetzt alle vorherigen Ausgaben.

Relevant R phrases (number and full text)

36/38	Irritating to eyes and skin.
43	May cause sensitisation by skin contact.
51	Toxic to aquatic organisms.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
------	-------------------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Systopp - Colerit EH 2 (Resin)**

Print date: 19.03.2020

Product code: 43.600.100

Page 8 of 8

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)